

(12) **United States Patent**
Denkins et al.

(10) **Patent No.:** **US 7,886,943 B1**
(45) **Date of Patent:** **Feb. 15, 2011**

(54) **DRYWALL JOINT COMPOUND PUMP WORKSTATION**

(75) Inventors: **Jeffrey L. Denkins**, Shawano, WI (US);
Steven J. Mondloch, Kaukauna, WI (US)

(73) Assignee: **Apla-Tech, Inc.**, Kaukauna, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 442 days.

(21) Appl. No.: **12/137,661**

(22) Filed: **Jun. 12, 2008**

Related U.S. Application Data

(60) Provisional application No. 60/943,957, filed on Jun. 14, 2007.

(51) **Int. Cl.**
B60P 3/22 (2006.01)

(52) **U.S. Cl.** **222/608; 222/63; 401/48**

(58) **Field of Classification Search** 222/608,
222/1, 609, 610, 611.1, 613, 614, 626, 181.1,
222/185.1, 63; 401/48, 195, 188 R, 16, 137,
401/108, 207

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

2,007,113 A * 7/1935 Staples 222/56
2,317,288 A * 4/1943 Mccubbin 239/150
3,940,065 A * 2/1976 Ware et al. 239/146
5,230,608 A * 7/1993 Januska 417/44.1
5,279,700 A * 1/1994 Retti 156/578

5,535,926 A * 7/1996 Blitz et al. 222/334
5,878,925 A * 3/1999 Denkins et al.
5,924,598 A * 7/1999 Bradshaw 222/63
6,070,808 A * 6/2000 Kildow 239/146
6,260,743 B1 * 7/2001 Mazzenga 222/611.2
6,419,773 B1 * 7/2002 Lauermann 156/71
6,428,287 B1 * 8/2002 Denkins et al. 417/360
6,793,428 B2 * 9/2004 Lithgow 401/48
7,367,515 B1 * 5/2008 Newman 239/150

* cited by examiner

Primary Examiner—Lien T Ngo

(74) Attorney, Agent, or Firm—Andrus, Sceaux, Starke & Sawall, LLP

(57) ABSTRACT

A portable drywall joint compound pump workstation has a joint compound supply reservoir with an open top and closed bottom removably attached to a wheeled framework. The workstation further has a pump assembly including a pump control removably connected to the framework for pumping joint compound from the supply reservoir to a workstation outlet extending from the pump control. The pump assembly includes a high pressure cylinder connected to a valve and quick coupling arrangement which, in turn, is in communication with the supply reservoir through the bottom end thereof. A discharge line extends between the high pressure cylinder and the pump control for feeding joint compound from the supply reservoir to the pump control. A first discharge port is provided on the pump control for continuously feeding a variety of drywall finishing tools. A second discharge port is provided on the pump control for supplying wash down water to clean tools or act as a source of high pressure fluid. A purge line runs between the pump control and the supply reservoir for priming, recirculating and mixing drywall compound in the reservoir.

8 Claims, 1 Drawing Sheet

